

TED UPS Line Interactive 700 LED

- Automatic voltage stabilization (AVR)
- Intelligent Start-up in DC mode (Cold Start Function)
- Automatic restart while AC is recovering
- High reliability microprocessor control
- Smart battery management
- Off-Mode charging
- LED Power indicator



Specifications	
Model	TED-700 TED003966
Power	700VA / 400W
Input	
Voltage range	140-290V AC
Frequency range	45-65Hz
Output	
AC Voltage Regulation	230V ± 9% AC
Frequency Range	50Hz ± 0.5%
Transfer Time	≤ 9ms
Waveform	Simulated Sine Wave
Battery	
Battery Type & Number	1x 12V 7.1Ah
Back-up Time	15 min.
Typical Recharge Time	7-15 h
Protections	
Protections	Full Protection: surge, overload / underload, discharge, overcharge, short-circuit, alarm
Class Protection	IP20
Physical Characteristics	
Output Receptacles	2x Schuko
Dimensions (L x W x H)	310 x 95 x 140 mm
Net Weight	5 kg
Operating Humidity / Temperature	0 - 90% / 0 - 40°C
Noise Level	<40dB
Management	
USB / RS-232 Port	Supports Windows XP, 7, 8, 10, Linux, Unix, BSD